



FINE 4025 PIXIE

FINE 4025 PIXIE is a 3IN1 LED moving head light with beam, wash and matrix effects. Using 25 PCS high-quality OSRAM RGBW 4IN1 40W LEDs, it distributes by 5*5 and single LED & color can be controllable.

It is well shown the wash effect through zoom range of $3.5^{\circ}\sim60^{\circ}$ and linear & smooth dimmer together with the situation of no flicker under low brightness light. It can work as a beam moving head light when the minimum angle is 3.5° . It can create rich and colorful beam effects with built-in macro functions. When it works as a matrix moving head light, it can show numbers, letters, lines, box and other shapes.



25pcs 40W OSRAM 4 IN1 LEDs Average Life Span > 50,000 h

OPTICAL SYSTEM

Beam Angle: 3.5° - 60° High-quality PMMA optical lens

COLOR SYSTEM

RGBW 4 in 1

EFFECT EQUIPMENT

All-optical domain dimming, 65536 grade dimming accuracy Fast strobe: 1-25Hz Preset 65 color macro functions Preset 64 effect macro functions

MOVEMENT PARAMETER

Pan & Tilt continuous rotation

CONTROL AND PROGRAMMING

Control Channel: 4 control channel models 22/36/98/123
Protocol: Standard DMX512, Artnet Ethernet Control Protocol; Optional: wireless DMX512
Menu display: 3.5 inches LCD display, resolution ratio: 128 x 64; Chinese and English languages can be switched freely; menu available to display 180° reversely; Noncontact roller operation; DMX Signal Connection: 3-pin XLR input/output

ELECTRONIC CONTROL

TECHNOLOGY

Fixture reset is controlled through menu or lighting console
0-100% dimmer
Constant current drive mode
Temperature sensor detection, intelligent adjustment for light source power
DMX channel level monitoring
Fixture information query
Intelligent fan adjustment
Initial brightness settings for all colors

POWER SUPPLY

AC100-240V 50/60Hz Input Power: 900W PE>0.95

SAFE PROTECTION

Over current, overvoltage and overheating protection

WORKING TEMPERATURE

- 10°C - 45°C

DIMENSION AND WEIGHT

Fixture Dimension: 504mm x 382mm x 657mm Package Dimension (flight case): 910mm x 550mm x880mm Net Weight: 29 kg (fixture) Gross Weight: 69.5 kg

PACKAGE

2pcs /flight case

IP RATE

IP 20