

CHAIN MASTER HOIST_BGV-D8 (Made in Germany)

The compact form, robust aluminum casing and low unladen weight of ChainMaster rigging lifts guarantee optimal handling in day-to-day use. An extensive selection of optional fittings and accessories allow worldwide use in line with the widest range of requirement criteria. In combination with ChainMaster control systems, we can offer all users – even for special applications – an all-in-one solution that leaves nothing to be desired.



Basic Features

- Climbing- or Standard Suspension
- Direct- or Contactor Control
- Light and compact Housing
- Precise Chain Guide
- 5-Pocket Chain Wheel
- Textile Chain Bag
- DC Brake
- Patented Friction Clutch for Overload Protection

BGV-D8 Electric Chain Hoists Chain with 1 fall

Capacity	Speed	Falls	Load chain in mm EN-818-7	Weight without chain	Dimension (in mm)
250 kg	4 m/min	1	4 x 12 mm	15 kg	317x189x114
320 kg	4 m/min	1	4 x 12 mm	15 kg	317x189x114
500 kg	4 m/min	1	5,2 x 15 mm	20 kg	453x218x124
1000 kg	4 m/min	1	7 x 22 mm	27 kg	371x257x155
1000 kg	8 m/min	1	7 x 22 mm	27 kg	417x257x155
1600 kg	4 m/min	1	9 x 27 mm	58 kg	503x342x197

Capacity	Speed	Falls	Load chain in mm EN-818-7	Weight without chain	Dimension (in mm)
2500 kg	4 m/min	1	11 x 31 mm	74 kg	533x342x209
2500 kg	8 m/min	1	11 x 31 mm	74 kg	533x342x209

BGV-D8 Electric Chain Hoists

Chain with 2 fall

Capacity	Speed	Falls	Load chain in mm EN-818-7	Weight without chain	Dimension (in mm)
500 kg	2 m/min	2	4 x 12 mm	15 kg	317x189x114
1000 kg	2 m/min	2	5,2 x 15 mm	21 kg	453x218x124
2000 kg	2 m/min	2	7 x 22 mm	27 kg	371x257x155
2000 kg	4 m/min	2	7 x 22 mm	27 kg	417x257x155
3200 kg	2 m/min	2	9 x 27 mm	58 kg	503x342x197
5000 kg	2 m/min	2	11 x 31 mm	74 kg	533x342x209
5000 kg	4 m/min	2	11 x 31 mm	74 kg	533x342x209

(All data is approximate; we cannot accept any liability for errors and omissions, and we reserve the right to make changes.)

China, Hong Kong & Macau Distributor : Epical Staging Technology Limited
(contact : sales@epical.com.hk / 852-3580 1846)